

Cassette Splitter (LGX Type)



DESCRIPTION

Cassette splitter feature small size and high reliability which can be mounted FDH & FDP. SC adapter is both input and output.

FEATURES

- Low Insertion Loss
- Low PDL (Polarization Dependent Loss)
- Compact Design
- Exceptional Reliability and Stability
- Wide Operating Wavelength: From 1260nm to 1650nm
- Wide Operating Temperature: From -40°C to 85°C

APPLICATION

- FTTX Systems
- LAN, WAN and Metro Networks
- Analog/Digital Passive Optical Networks
- CATV Networks
- Other applications in fiber optic systems

AVAILABLE RATIO

1:2/1:4/1:8/2:4/2:8	130x100x25
1:16/2:16	130x100x50
1.32/2.32	130x100x102
1x16/2:64	130x100x200
1/2:32 H Layout	266x100x50
1/2:64 H Layout	266x100x102

STANDARD PLANAR SPLITTER

Wavelength	1260-1650nm		1310nm / 1550nm
	Max. LB (db)	Uniformity (db)	PDL (db)
1x2	4.1	0.7	0.2
1x4	7.3	0.7	0.2
1x8	10.4	1.0	0.2




 **Manufacturing Unit: 1**
Vapi, Gujarat

Saibaba Infocom Pvt.Ltd.
Plot No. 67 & 70, Daman
Ganga Ind. Park, Village,
Karvad, Vapi dist.- Valsad,
Gujarat (396191)

 **Manufacturing Unit: 2**
Coimbatore, Tamil Nadu

Saibaba Infocom Pvt.Ltd.
181, T K Nagar, Tirampalli,
Coimbatore,
Tamil Nadu: 641033.

 **Corporate & Head Office:**
Synfocom Systems LLP

Prime Plaza, Behind Kalki Fashion Store,
SV Rd, Santacruz West, Mumbai,
Maharashtra 400054

 **dr.com**
PATCH PERFECT

Registered
Trademark of



SAIBABA INFOCOM
PVT.LTD

Follow us on:



@drcomindia

 **Toll Free: 1800-267-3866**

 **info@dr-com.in**

 **www.dr-com.in**