

DRC 2GE+1POTS+AC WiFi DR-323DAC



Dual Mode



HGU Management



Route



Productoverview

2GE+1POTS+WiFi GPON/EPON HGU terminal devices are designed for fulfilling FTTH and triple play service demand of fixed network operators. These boxes are based on the mature technology, which have high ratio of performance to price, and the technology of IEEE802.11b/g/n/ac WIFI, Layer 2/3, and high quality VoIP as well. Support full management of HGU devices through DRC OLT. They are highly reliable and easy to maintain, with guaranteed QoS for different service. And they are fully compliant with technical regulations such as IEEE802.3ah, ITU-T G.984.x and technical requirement of GPON Equipment (V2.0 and above version)

Product	Uplink interface	User interface
HGX-323DAC-BC	1*EPON/GPON	2*GE+1*POTS + Dual WiFi




Special Features

- **Support full management of HGU functions by DRC OLT**
- **Plug and play, features auto-detecting, auto-configuration, and auto firmware upgrade ,etc**
- **Integrated OAM/OMCI remote configuration and maintenance function**
- **Support rich QinQ VLAN functions and IGMP Snooping multicast features**
- **Fully compatibility with OLT based on Broadcom/PMC/Cortina chipset**
- **Support 802.11n/ac WiFi (4T4R)function**
- **Support NAT, Firewall function**
- **Support IPv4 and IPv6 dual stack**
- **Support SIP protocol**
- **Integrated line testing compliant with GR-909on POTS**



Functional Characteristics

Product appearance features





Technical Indicator

Technical item	2GE+1POTS(option)+WiFi
PON interface	1 G/EPON port(EPON PX20+ and GPON Class B+) Receiving sensitivity: $\leq -28\text{dBm}$ Transmitting optical power: $0 \sim +4\text{dBm}$ Transmission distance: 20KM
Wavelength	Tx1310nm,Rx 1490nm
Optical interface	SC/UPC connector
LAN interface	2 x 10/100/1000Mbps auto adaptive Ethernet interfaces, Full/Half, RJ45 connector
POTS interface	1 x RJ11 connectors Support: G.711A/G.711U/G.723/G.729 codec Support: T.30/T.38/G.711 Fax mode, DTMF Relay
WiFi interface	Compliant with IEEE802.11b/g/n/ac 2.4GHz Operating frequency: 2.400-2.483GHz 5.0GHz Operating frequency: 5.150-5.825GHz Support MIMO, 4T4R,5dBi external antenna, rate up to 1.167Gbps Support: multiple SSID TX power: 11n--22dBm/11ac--24dBm
LED	9, For Status of POWER _s LOS _s PON _s WAN _s LAN1 _s LAN2 _s 2.4G _s 5G _s PHONE
Operating condition	Temperature: $0^{\circ}\text{C} \sim +50^{\circ}\text{C}$ Humidity: $10\% \sim 90\%$ non-condensing ³
Storing condition	Temperature: $-30^{\circ}\text{C} \sim +60^{\circ}\text{C}$ Humidity: $10\% \sim 90\%$ non-condensing ³
Power supply	DC 12V/1A
Power supply	$\leq 10\text{W}$
Dimension	178mm×120mm×30m(L×W×H)
Net weight	0.32Kg



Technical Indicator

LED information

LED	ON	Blink	OFF
PWR	The device is powered up	—	The device is powered down
PON	Green is registered to the PON system	Green is registering to the PON system	Green is not registered to the PON system
LOS	Device does not receive optical signals	—	Device have received optical signals
WAN	Route WAN connect to internet.	—	Router WAN do not connect to internet.
WiFi(2.4/5.0G)	WiFi turned on	WiFi turn on and with ongoing data transmission	Device is power off or WiFi turned off
PHONE	Device has registered to the soft-switch, but without ongoing data transmission	Phone hooks of for the port is with ongoing data transmission	Device is power off or not registered to the soft-switch
LAN1~ LAN2	Port is connected properly	Port is sending or/and receiving data	Port connection exception or not connected NA User is accessing User is logged in User has no access



Software Function

Management Mode

- **OAM/OMCI s Telnet s WEB s TR069**
- **Support full management of HGU functions by DBCOLT**

Data Service Functions

- Full speed non-blocking switching
- 2K MAC address table
- 64 full range VLANID
- Support QinQ VLAN, 1:1 VLAN, VLAN reusing, VLAN trunk, etc
- Integrated port monitoring, port mirroring, port rate limiting, port SLA, etc
- Support auto polarity detection of Ethernet ports (AUTOMDIX)
- Integrated IEEE802.1p QoS with four level priority queues
- Support IGMP v1/v2/v3 snooping/proxy and MLDv1/v2 snooping/proxy
- Support bridge, router and bridge/router mixed mode

WiFi Service Functions

- Integrated 802.11b/g/n/ac
- Support max 128 users
- Authentication : WEP/WAP-PSK(TKIP)/WAP2-PSK(AES)
- Modulation type: DSSS s CCK and OFDM
- Encoding scheme: BPSK s QPSK s 16QAM and 64QAM




Software Function

POTS Service Function

- Call protocol: SIP(IMS compatible)seamless compatible with all popular call agent
- Integrate heartbeat function and support active/standby call agent
- Voice coding: ITU-T G.711/G.722/G.729, auto-negotiate with call agent
- Echo cancellation exceeding ITU-T G.165/G.168-2002, upto 128ms tail length
- Support high/low speed fax, bypass fax, and T38fax
- Support high speed MODEM(56Kbps) dial access
- Support RFC2833 and redundant RFC2833, difference rings, MD5 authentication, call forward, call waiting, hot-line call, alarm clock, and all kinds of value-added voice service
- Multi-party conferencing
- IP address assignment: dynamic PPPoE/DHCP Client and static IP
- SupportWEBsCLIsIVRsTR069
- Call loss less than0.01%



Typical Application Diagram






Specification Subject to Change without notice.



 **Corporate & Head Office:**

Prime Plaza, Behind Kalki Fashion
Store, SV Rd, Santacruz West,
Mumbai, Maharashtra 400054

Follow us on:      @drcomindia

 info@dr-com.in  **Toll Free:** 1800-267-3866  www.dr-com.in