

# FIBRE SLEEVES



***Fibre sleeve** is composed of a steel strength member, inner fibre tube and outer shrink tube, two clear outer tubes for viewing the color of the optical fibre itself. These sleeves are designed to fit smaller width splice trays while still accommodating both 250 m and 900 m fibres*

## Features:

- *Slim sleeves feature reduced diameter to fit more finished product in splice trays*
- *Sleeves feature clear outer tube for viewing fiber color*
- *Precise lengths free of all burrs and sharp edges*
- *Choice of lengths and diameters*
- *Heat-bonded assembly*

## Application:

Standard & Slim styles,

Stainless-Steel Strength

Maximum Protection from  
Shock & Vibration.

Polyolefin Copolymer

## Specification:

*Fiber Splice Sleeves shall meet the requirement for **dr.com**<sup>®</sup> specification. Outer tubing shall meet MIL-I-23053/5 class requirement. The sleeves shall feature a stainless steel strength member, polyolefin copolymer inner tube & polyolefin outer tube with precise cut length & smooth ends. Sleeves shall be ,available in standard, slim, mini & micro styles*



## Features:

- Outer tube of the splice sleeves meets MIL-I-23053/5 Class 2.
- Standard style sleeves meet **dr.com**® specifications.

## Specification:

<i>Dimensions</i>	<i>Dimensions</i>
<i>Outer Tube</i>	<i>Polyolefin</i>
<i>Working Temperature</i>	<i>-55° C to 135° C (-65° F to 275° F)</i>
<i>Ultimate Strength</i>	<i>220 kg/cm2</i>
<i>Elongation</i>	<i>650%</i>
<i>Specific Gravity</i>	<i>0.95</i>
<i>Water Absorption</i>	<i>0.05%</i>
<i>Minimum Shrink Temp</i>	<i>95° C (203° F)</i>
<i>Fungus Resistance</i>	<i>Inert</i>
<i>Solvent Resistance</i>	<i>Good</i>
<i>Acid Resistance</i>	<i>Excellent</i>
<i>Inner Tube</i>	<i>Polyolefin Copolymer (Ethylene-Vinyl Acetate)</i>
<i>Ultimate Strength</i>	<i>200 kg/cm2</i>
<i>Elongation</i>	<i>700%</i>
<i>Melting Point</i>	<i>80° C (176° F)</i>
<i>Specific Gravity</i>	<i>0.93</i>
<i>Strength Member</i>	<i>302 Stainless Steel with rounded &amp; polished ends</i>
<i>Shrink Time*</i>	<i>Standard: 90 seconds</i>
<i>Shrink Size</i>	<i>Standard: 2.9 mm</i>




# OUR CATEGORIES



**FIBRE CABLES**



**OPTICAL  
PATCH CORD**



**FTTH  
PATCH CORD**



**ACCESSORIES**



**GPON-ONT**



**HOUSING  
SOLUTIONS**



**R6G CABLES**



**SMART UPS**



**USB HUB**



**CONNECTORS**



**COPPER  
PATCH CORDS**




**FIBRE  
PIGTAILS**



**FIBRE SLEEVES**



**FMS**



**COPPER CABLES**



**DOME BAMBOO**



**SFP  
TRANSCEIVERS**

# THANK YOU

## Contact Us

### **Manufacturing Unit: 1 Vapi, Gujarat**

**Saibaba Infocom Pvt. Ltd.**  
Plot No. 67 & 70, Daman  
Ganga Ind. Park, Village,  
Karvad, Vapi dist.- Valsad,  
Gujarat (396191)

### **Manufacturing Unit: 2 Coimbatore, Tamil Nadu**

**Saibaba Infocom Pvt.Ltd. 181,**  
T K Nagar, Tirampalli,  
Coimbatore,  
Tamil Nadu: 641033.

### **Corporate & Head Office: Mumbai**

**Synfocom Systems LLP**  
Prime Plaza, Behind Kalki  
Fashion Store, SV Rd,  
Santacruz West, Mumbai,  
Maharashtra 400054